



Husqvarna TS 60

A robust tile saw with a refined cart and rail system for perfectly straight cuts. The TS 60 is equipped with the innovative and patented Jet Stream Water Containment System, which means the water and slurry stay in the cart during cutting. By way of a stream of water that passes through the trench in the cart, slurry is minimised and the area around the saw stays clean and free of water spray. At the same time, the blade is cooled and lubricated prior to cutting.



DIVERSE SAWING

With the TS 60 you can do both plunge and mitre cuts.



EASY TO HANDLE

Low weight and foldable legs make it easy to carry. Stable wheels facilitate transportation around the working site.



JET STREAM SYSTEM

The Jet Stream Water Containment System keeps water and slurry in the cart trench for a clean work area.



RECYCLING WATER SYSTEM

A recycling system cleans water that can be reused.

Features Husqvarna TS 60

- Equipped with Elgard™ which indicates via an LED when the machine is overloaded, to prevent motor damage and increase motor life.
- The maximum cutting length of 700 mm and the 610 x 410 mm cutting table allows you to cut eg. 500 x 500 mm tiles on the diagonal.
- An adjustable cutting head enables bevel cuts between 22.5 and 45 degrees.
- Removeable table, angle guide and adjustable-height stand are included as standard equipment.
- Husqvarna-designed 1200 W motor.
- Weighing just 36 kg, it's easy to carry and transport.
- Electronic SoftStart™ allows starts with normal slow-acting fuses.
- Efficiently switches between plunge cuts and mitre cuts with ease.
- The TS 60's features and benefits deliver greater workplace flexibility for contractors. Now it's possible to cut indoors, thanks to the Jet Stream Water Containment System.

TECHNICAL SPECIFICATION	
Motor manufacturer	Husqvarna
Phases	1
Spindle diameter	15.9 mm / 0.625 "
Blade diameter	250 mm / 10 inch
Max cutting depth	65 mm / 2.75 inch
Max cutting length	700 mm / 28 inch
Max tile size for diagonal cutting	508 mm / 20 "
Water tank volume	12.4 lit / 3.28 gal.
Weight (excl. cutting equipment)	36 kg / 79 lbs
Product size, LxVxH	932x700x468 cm / 37x28x18 inch
Dimensions crated (LxVxH)	1016x558.8x711.2 mm / 40x22x28 "
Weight incl. packaging	49.44 kg / 109 lbs

